

SM-75/PM-30

STAGE MONITOR

PERSONAL MONITOR

Step Into Tomorrow's Music
KORG



Digital Ready Realism



The Monitors Built for Digital Music



SM-75 STAGE MONITOR

Advanced full range speaker units with powerful 11,000 gauss magnets bring out the fine detail of your instrument's sound. Introducing the PM-30 and SM-75, two new monitors dedicated to accurate reproduction of today's digital music. For personal keyboard monitoring and multi-track recording, you'll like the compact size of the PM-30. Powered by 25W (45W music) of clean amplification, this monitor is at the top of its class. Yet it can be

mounted on a microphone stand for space saving local

SM-75 Specifications ■ Rated output: 75W ■ Music output: 130W ■ Total harmonic distortion: 0.1% or less (at 1kHz, rated output, into 8 ohms) ■ Frequency response: 75Hz - 20kHz ■ Efficiency (sensitivity): 98dB/W/m ■ Maximum SPL: 119dB ■ Input jacks: line in x 4 ■ Input level: 300mV for rated output ■ Input impedance: 47k ohms ■ Output jack: line out x 1 (20Hz - 20kHz ± 1dB) ■ Speaker units: 110mm diameter full range x 4 ■ Control facilities: Volume x 1; Tone control x 3: (High: 10kHz ± 15dB; MID: 1kHz ± 15dB; LOW: 100Hz ± 15dB) ■ Power supply: AC local voltage ■ Power consumption: 59W ■ Dimensions: 430(W) x 310(H) x 220(D)mm ■ Weight: 11.2kg ■ Supplied accessories: AC cord

coverage. For on-stage clarity look to the SM-75. This uses four of the same 110mm 11,000 gauss speaker units employed in the PM-30. Its highly stable amplifier circuitry pumps out 75W (130W music). Connections are versatile with the SM-75's four inputs and line output. 3-Way tone controls let you tailor the response to suit the situation.


PM-30 Specifications ■ Rated output: 25W ■ Music output: 45W ■ Total harmonic distortion: 0.1% or less (at 1kHz, rated output, into 8 ohms) ■ Frequency response: 80Hz - 20kHz ■ Efficiency (sensitivity): 92dB/W/m ■ Maximum SPL: 108.5dB ■ Input jacks: line in x 2 ■ Input level: 300mV for rated output ■ Input impedance: 30k ohms ■ Output jack: line out x 1 ■ Speaker units: 110mm diameter full range x 1 ■ Power supply: AC local voltage ■ Power consumption: 21W ■ Dimensions: 230(W) x 160(H) x 220(D)mm ■ Weight: 4.9kg ■ Supplied accessories: AC cord

PERSONAL MONITOR

PM-30



REAR PANEL



SM-75/PM-30 Options

- Number cord 3m/5m/7m
- Stereo connection cord
- Stand for SM-75 ST-75

An ultra-compact monitor with built-in battery powered amplifier. The TM-03 gives you great, portable sound not only with your instrument but with cassette decks as well.



TM-03 TABLE MONITOR

NOTICE

Korg products are manufactured under strict specifications and voltages required by each country. These products are warranted by the Korg distributor only in each country. Any Korg product not sold with a warranty card or carrying serial number disqualifies the product sold from the manufacturer's/distributor's warranty and liability. This requirement is for your own protection and safety.

KORG

KEIO ELECTRONIC LABORATORY CORPORATION
15-12, Shimotakaido 1-chome, Suginami-ku, Tokyo Japan.

*Specifications and features are subject to change without notice for further improvement